

Standard models		Fax your order to fax +358-9-670 208
Ordercode	Application	Note
2x6 DF *	3G conformity, GSM450-PCS, RF to RF	LO + 140 MHz, digital IQ model
2x10 DF	3G conformity + deployment, RF to RF	LO + 140 MHz, digital IQ model
2x6 D	GSM450-PCS1900, 50 ns, RF to RF	LO + 140 MHz, digital IQ model
2x3 D	CDMA, 50 ns, RF to RF	LO + 140 MHz, digital IQ model
2x6 DIF	DVB-T, TETRA, 50 ns delay, IF interface	No LO, custom IF interface
2x6 MIL	VHF, Defence Communications	LO + 140 MHz, digital IQ model

* *Recommended*

D= digital I/Q system, F= 1ns delay FIR included

All included:

- SOFILINK-kit (PCI- or PCCARD-adapter, cable, 3.5" software for Windows 9x)
- Warranty 36 months from shipment date
- Support by phone, fax and email FREE
- Delivery in 6 weeks from received order (fax +358-9-670208) - Carton Container for shipment
- operation manual, calibration, calibration certificate, Factory Acceptance Test (in english)

Options	
Description	Option Code
Integrated Local Oscillators	ILO
EXTra programmable ATTenuator, range 0-127 dB, pair, free in DF *	EXTATT127
Pre-installed SOFILINK and notebook PC bundle	PC
inbuilt PC with 10.4" TFT-display, PS/2 connectors *	IPC
Dynamic Fading Sequence External Trigger Connectors	DFSETC
Adjustable input level 0...-40 dBm, output 0...-40 dBm *	AGC2
Local Oscillator input level +9 dBm (instead of +13 dBm)	LO9
Accrediated calibration according to EN45001 (free standard calibration)	ACAB
Costs Insurance Paid (CIP) shipment to Europe	CIP-EU
Costs Insurance Paid (CIP) shipment to USA and ASIA	CIP

AFTER SALES SERVICE	
Note: outside valid warranty period. Add transport costs	Servicecode
Calibration and operational check.	CAL
Calibration + Factory Acceptance Test + minor Repair	SERVICEPACK

Test Accessories	
Description	Ordercode
attenuator 10 dB	NAT-10-60
attenuator 15 dB	NAT-15-30
amplifier 20 dB	ZFL-2000
amplifier 28 dB	ZFL-2500
power splitter	ZAPD-30-S
6 microwave cables RG142	MWKIT6
hard shipping case / protector case	1660